




Measurement Report

Customer/用户名称:	Voltage/电压: 450 V			
Product name/产品名称: 铝电解电容器	Capacitance/电容量: 5600 μ F			
Product series/产品系列: B43340	Size/尺寸: Φ 90 MM x 158 MM(h)			
Measurerequirement/测试条件: Temperature/温度: $25 \pm 5^\circ\text{C}$ Humidity/湿度: $60 \pm 15\%$ Frequency/频率: 120HZ, Lctestvoltage/漏电流测试电压: 450V, Lc testtime/漏电流测试时间: 5 min(分)				
Quantity/数量: 12		Quantity Check/检验数量: 10		
No.	Cap. (μ F)	Tan δ (%)	Lc (5mA)	Esr (30m Ω)
Test Standard value/ 测试标准值	- 20 % ~ + 20 % 5000 μ F ~ 6100 μ F	≤ 20	≤ 5	≤ 55
1	5400	4.75	1.13	16.1
2	5348	4.74	1.19	15.8
3	5547	4.75	1.12	15.1
4	5472	4.79	1.16	15.7
5	5387	4.77	1.06	15.9
6	5421	4.83	1.14	15.1
7	5397	4.79	1.08	15.9
8	5417	4.78	1.14	15.0
9	5394	4.75	1.07	16.1
10	5451	4.74	1.20	15.2
Visual: No leakage, right polarity, clearly marking, no break on sleeve, appearance of product is ok. 外观: 产品无漏液, 套管收缩均匀, 字体清晰, 无明显污迹, 破裂。				
Remark: 备注:				
Check Date/检验日期: 2025.03.15				
Measure result/检验结论: 合格				
检验 人: 黎传震	Checked/审核: 王小凤	Approval/确认: 出货QC		

出厂检验报告



**EPCOS Ltd., A TDK Group
Company**