



6 PIN DIP PHOTOTRANSISTOR PHOTOCOUPLED TIL11X Series MCT2X Series



Schematic



Pin Configuration

- TIL11X series: TIL111, TIL117
- MCT2X series: MCT2, MCT2E
- High isolation voltage between input and output
Viso = 5000 Vrms
- Creepage distance >7.6mm
- Compact dual-in-line package
- Operating temperature up to +110°C
- The product itself will remain within RoHS compliant version
- Compliance with EU REACH
- UL and cUL approved (No. E214129)
- VDE approved (No. 132249)
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved
- CQC approved

1. Anode
2. Cathode
3. No Connection
4. Emitter
5. Collector
6. Base

Description

The TIL11X series and MCT2X series of devices each consist of an infrared emitting diode optically coupled to a phototransistor detector.

They are packaged in a 6-pin DIP package and available in wide-lead spacing and SMD option.

Applications

- Power supply regulators
- Digital logic inputs
- Microprocessor inputs
- Appliance system
- Industrial controls

Absolute Maximum Ratings (Ta=25°C)

| | Parameter | Symbol | Rating | Unit |
|--------|-------------------------------------|------------------|------------|-------|
| Input | Forward current | I _F | 60 | mA |
| | Peak forward current (t = 10μs) | I _{FM} | 1 | A |
| | Reverse voltage | V _R | 6 | V |
| | Power dissipation | P _D | 100 | mW |
| Output | Derating factor (above 100°C) | | 3.8 | mW/°C |
| | Collector-Emitter voltage | V _{CEO} | 80 | V |
| | Collector-Base voltage | V _{CBO} | 80 | V |
| | Emitter-Collector voltage | V _{ECO} | 7 | V |
| | Power dissipation | P _C | 150 | mW |
| | Derating factor (above 100°C) | | 9.0 | mW/°C |
| | Total Power Dissipation | P _{TOT} | 200 | mW |
| | Isolation Voltage* ¹ | V _{ISO} | 5000 | V rms |
| | Operating Temperature | T _{OPR} | -55 to 110 | °C |
| | Storage Temperature | T _{STG} | -55 to 125 | °C |
| | Soldering Temperature* ² | T _{SOL} | 260 | °C |

Notes:

*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2 & 3 are shorted together, and pins 4, 5 & 6 are shorted together.
*2 For 10 seconds

Electro-Optical Characteristics (Ta=25°C unless specified otherwise)

Input

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Condition |
|-----------------|----------------|----------------|------|------|------|---------------------------------|
| Forward voltage | TIL111 | - | 1.22 | 1.4 | | $I_F = 16mA$ |
| | | - | - | 1.4 | | $T_A=0-70^\circ C, I_F = 16mA$ |
| | TIL117 | V _F | 1.32 | - | V | $T_A = -55^\circ C, I_F = 16mA$ |
| | | - | 1.1 | - | | $T_A=110^\circ C, I_F = 16mA$ |
| MCT2 MCT2E | - | 1.23 | 1.5 | | | $I_F = 20mA$ |
| | I _R | - | - | 10 | μA | $V_R = 6V$ |

Output

| Parameter | Symbol | Min | Typ. | Max. | Unit | Condition |
|--|-------------------|--------|------|------|------|---|
| Collector-Base dark current | I _{CBO} | - | - | 20 | nA | $V_{CB} = 10V$ |
| Collector-Emitter dark current | I _{CEO} | - | 1 | 50 | nA | $V_{CE} = 10V, I_F = 0mA$ |
| | | TIL117 | - | 0.2 | 50 | $V_{CE} = 30V, I_F = 0mA, T_A = 70^\circ C$ |
| Collector-Emitter breakdown voltage | BV _{CEO} | 80 | - | - | V | $I_c = 1mA$ |
| Collector-Base breakdown voltage | BV _{CBO} | 80 | - | - | V | $I_c = 0.01mA$ |
| Emitter-Collector breakdown voltage | BV _{ECO} | 7 | - | - | V | $I_E = 0.1mA$ |
| Emitter-Base breakdown voltage | BV _{EBO} | 7 | - | - | V | $I_E = 0.1mA$ |

* Typical values at $T_a = 25^\circ C$

Transfer Characteristics

| Parameter | Symbol | Min | Typ. | Max. | Unit | Condition |
|---|--------------------|-----|------|------|------|-----------------------------|
| Collector current (Phototransistor operation) | | 2 | - | - | mA | $I_F = 16mA, V_{CE} = 0.4V$ |
| Collector current (Photodiode operation) | I _{C(ON)} | | | | | |
| Current Transfer Ratio | TIL111 | 7 | - | - | μA | $I_F = 16mA, V_{CB} = 0.4V$ |
| | MCT2 MCT2E | 50 | - | - | % | $I_F = 10mA, V_{CE} = 10V$ |
| | | 20 | - | - | | $I_F = 10mA, V_{CE} = 10V$ |

Transfer Characteristics

| Parameter | Symbol | Min | Typ. | Max. | Unit | Condition |
|---|------------------|----------------------|------|------|-------------|---|
| Collector-Emitter saturation voltage | All | - | - | 0.4 | V | $I_F = 16\text{mA}, I_C = 2\text{mA}$ |
| | TIL117 | $V_{CE(\text{sat})}$ | - | 0.4 | | $I_F = 10\text{mA}, I_C = 0.5\text{mA}$ |
| Isolation resistance | R_{IO} | 10^{11} | - | - | Ω | $V_{IO} = 500\text{Vdc}$ |
| Input-output capacitance | C_{IO} | - | - | 2 | pF | $V_{IO} = 0, f = 1\text{MHz}$ |
| Turn-on time | TIL117 | T_{on} | - | 10 | 12 | |
| Turn-off time | TIL117 | T_{off} | - | 9 | 12 | |
| Rise time | TIL117 TIL111 | t_r | - | 6 | 10 | μs $V_{CC} = 10\text{V},$ $I_C = 2\text{mA}, R_L = 100\Omega$ |
| Fall time | TIL117 TIL111 | t_f | - | 8 | 10 | |
| Turn-on time | MCT2 MCT2E | T_{on} | - | 3 | 10 | |
| Turn-off time | MCT2 MCT2E | T_{off} | - | 3 | 10 | |
| Rise time | MCT2 MCT2E | t_r | - | 3 | 10 | μs $V_{CC} = 10\text{V},$ $I_F = 10\text{mA}, R_L = 100\Omega$ |
| Fall time | MCT2 MCT2E | t_f | - | 3 | 10 | |

* Typical values at $T_a = 25^\circ\text{C}$

Typical Electro-Optical Characteristics Curves









Figure 7. Collector-Emitter Saturation Voltage vs Collector Current




Figure 8. Switching Time vs Load Resistance




Figure 9. Turn-on Time vs Base-Emitter Resistance




Figure 10. Turn-off Time vs Base-Emitter Resistance






Figure 11. Switching Time Test Circuit & Waveforms

Order Information

Part Number

TIL11XY(Z)-V

or

MCT2XY(Z)-V


Note

X = Part no. for MCT2X series (E or none)
= Part no. for TIL11X series (1 or 7)
Y = Lead form option (S, S1, M or none)
Z = Tape and reel option (TA, TB or none).
V = VDE safety (optional)


| Option | Description | Packing quantity |
|---------|---|---------------------|
| None | Standard DIP-6 | 65 units per tube |
| M | Wide lead bend (0.4 inch spacing) | 65 units per tube |
| S (TA) | Surface mount lead form + TA tape & reel option | 1000 units per reel |
| S (TB) | Surface mount lead form + TB tape & reel option | 1000 units per reel |
| S1 (TA) | Surface mount lead form (low profile) + TA tape & reel option | 1000 units per reel |
| S1 (TB) | Surface mount lead form (low profile) + TB tape & reel option | 1000 units per reel |

Package Dimension (Dimensions in mm)


Standard DIP Type




Option M Type




Option S Type



Option S1 Type



Recommended pad layout for surface mount leadform



Notes

Suggested pad dimension is just for reference only.
Please modify the pad dimension based on individual need.

Device Marking





Notes

| | |
|--------|--|
| T | denotes Factory No code : made in China T : made in Taiwan |
| EL | denotes Everlight |
| TIL117 | denotes Device Number |
| Y | denotes 1 digit Year code |
| WW | denotes 2 digit Week code |
| V | denotes VDE optional |



Tape & Reel Packing Specifications

Option TA




Direction of feed from reel

Option TB



Direction of feed from reel

Tape dimensions




| Dimension No. | A | B | Do | D1 | E | F |
|----------------|-----------|-----------|-----------|------------|----------|----------|
| Dimension (mm) | 10.8±0.1 | 7.55±0.1 | 1.5±0.1 | 1.5+0.1/-0 | 1.75±0.1 | 7.5±0.1 |
| Dimension No. | P0 | P1 | P2 | t | W | K |
| Dimension (mm) | 4.0±0.15 | 12±0.1 | 2.0±0.1 | 0.35±0.03 | 16.0±0.2 | 4.5±0.1 |

Precautions for Use

1. Soldering Condition

1.1 (A) Maximum Body Case Temperature Profile for evaluation of Reflow Profile



Note:

Reference: IPC/JEDEC J-STD-020D

Preheat

Temperature min (T_{smin})

150 °C

Temperature max (T_{smax})

200°C

Time (T_{smin} to T_{smax}) (t_s)

60-120 seconds

Average ramp-up rate (T_{smax} to T_p)

3 °C/second max

Other

Liquidus Temperature (T_L)

217 °C

Time above Liquidus Temperature (t_L)

60-100 sec

Peak Temperature (T_p)

260°C

Time within 5 °C of Actual Peak Temperature: $T_p - 5°C$

30 s

Ramp- Down Rate from Peak Temperature

6°C /second max.

Time 25°C to peak temperature

8 minutes max.

Reflow times

3 times

DISCLAIMER

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
3. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
4. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.
5. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.
6. Statements regarding the suitability of products for certain types of applications are based on Everlight's knowledge of typical requirements that are often placed on Everlight products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Everlight's terms and conditions of purchase, including but not limited to the warranty expressed therein.